DELMONT POOL EQUIPMENT






W SERIES BOBBIN SIDE MOUNT SAND FILTER

Delmont sand filter is all about strength and reliability. The filter tank is made of high-quality fiberglass and resin with a high-pressure capability. The outer layer is continuously wound with fiberglass strands to create a high strength vessel. The tank is UV resistance on the surface and the whole filter has a good resistance to chemical and sunlight. The multiport valve is mounted on the side for easy reach. The maximum working pressure is 36 psi or 2.5 bar. The maximum working temperature is 43° Celsius or 109° Fahrenheit.

- Designed for high performance and long wearing application
- Exceptionally clear water quality
- Easy to maintain, clean and use
- Inner component materials are made of the latest generation of plastic resin



CODE	DESCRIPTION	PORT	FLOW	POOL	SAND	Α	В	С	D	E	F
			RATE	VOL.	(KG)	(MM)	(MM)	(MM)	(MM)	(MM)	(MM)
			(m/h)	(m/8hr)							
DFL00031	800mm (32")	2"	24.1	192.8	355	570	650	980	425	800	710
DFL00032	900mm (36")	2"	29.7	237.6	470	640	730	1110	480	900	710
DFL00033	1000mm (40")	2"	40.2	321.6	620	700	770	1190	580	1000	710
DFL00034	1100mm (44")	2"	42.0	336.0	700	740	820	1290	680	1100	890
DFL00035	1200mm (48")	2"	52.8	422.4	860	780	860	1380	740	1200	890
DFL00036	1400mm (56")	2"	57.0	456.0	1400	820	900	1590	800	1400	1200